WELL STATUS RECORD

FIELD: ZUIDWIJK | PLATFORM: | BLOCK: | WELL NO. ZWK-01

TAQA

WELL TYPE :	GAS PRODUCER	RTE :	8.82	MAXIMUM DOGLEG :	4.17	AT	3092.70
FIRST COMPLETED :	APRIL 2012	LAT :		MAXIMUM DEVIATION :	24.87	AT	2110
WORKOVER DATE :		KOP :		MINIMUM I.D. :	2.75"	AT	88.78
WORKOVER NUMBER :		HUD :		AV. ANG. THRU PAY :	8		
ANNULUS FLUID :	Brine	TBG HANGER :	8.82	UNITS:	meters		
FLUID WEIGHT :	1.04 SG	REF. LOG :					

CASING DATA

SIZE (in)	WT (lb/ft)	GRADE	CONN.	TOP	MD	TVD
20"	0.625"	X56	S-60D/MT	Driven	80	80
9 5/8"	47/53.5	L80	TBLUE	SURFACE	998	

WELLHEAD DATA

	MAKER	TYPE	BORE (in)	FLANGES (in)	RATING (psi)
XMAS TREE	Cameron	SSMC	5.0	11.5"	5K
WELLHEAD	Cameron	SSMC	5 1/8		5K
TUBING SPOOL	Cameron	SSMC			5K
TUBING HANGER	Cameron	SSMC	4.791		5K

TUBING DATA

SIZE (in)	JOINTS	WT (lb/ft)	GRADE	THREAD TYPE
3 1/2"		9.2	L80-13Cr	TBLUE

LINER DATA

SIZE (in)	WT (lb/ft)	GRADE	CONN.	TOP	MD	TVD
7"	29/32	L80	TBLUE	898	2821	

MD RKB (m)	TVD RKB (m)	DESCRIPTION	MAKER TYPE	MIN ID	MAX OD	DRIFT	LENGTH	MATERIAL ELASTOMER	OTHER INFO
8.82	8.82	TUBING HANGER	CAM SSMC	5.000	14.030	2.867	0.75		3 1/2" BPV in Tubing Hanger Thread
9.57	9.57	PUP JOINT 3 1/2" 9.2#	TBLUE	2.992	3.500	2.867	2.02	L80-13Cr	
11.59	11.59	TUBING 3 1/2" 9.2#	TBLUE	2.992	3.500	2.867	74.38	L80-13Cr	
88.78	88.78	PUP JOINT 3 1/2" 9.2#	TBLUE	2.992	3.500	2.867	2.926	L80-13Cr	
88.78	88.78	TRSCSSV 3 1/2"	HAL NE, 7.5K	2.75		2.75	1.455	NI alloy 925	Plug gezet in SV 2.75" PX Plug
90.23	90.23	PUP JOINT 3 1/2" 9.2#	TBLUE	2.992	3.500	2.867	2.923	L80-13Cr	
93.15	93.15	TUBING 3 1/2" 9.2#	TBLUE	2.992	3.500	2.867	2977.13	L80-13Cr	
905.60	880.49	TOP OF 7" LINER							
1005.59	973.43	9 5/8" SHOE							
2125		TOP OF CEMENT COMPLETION							
2650	2492.06	7" LINER SHOE							
3070.62	2909.18	PUP JOINT 3 1/2" 9.2#	TBLUE	2.992	3.500	2.867	6.06	L80-13Cr	
3076.68	2915.20	LANDING NIPPLE 2.75	HAL 'R'	2.75	3.500	2.750	0.30	1CR-1MO	Plug gezet in Nipple 2.75" PR Plug
3076.98	2915.50	PUP JOINT 3 1/2" 9.2#	TBLUE	2.992	3.500	2.867	6.298	L80-13Cr	Tubing onder plug gevuld met water.
3083.28	2921.77	TUBING 3 1/2" 9.2#	TBLUE	2.992	3.500	2.867	173.126	L80-13Cr	
3139	2977.35	TOP RESERVOIR							
3268.84	3107.03	FLOAT / LANDING COLLAR 3 1/2"	WEATHERFORD	2.992	3.500	2.867	0.50	L80-13Cr	
3269.25	3107.44	TUBING 3 1/2" 9.2#	TBLUE	2.992	3.500	2.867	24.189	L80-13Cr	
3294	3132.19	FLOAT SHOE 3 1/2"	HAL	2.992	3.500	2.867	0.39	L80-13Cr	
3300	3138.19	TD							

COMMENTS

COMMENTS:

Elevations:
RT - NAP : 5.57 m
RT - Ground Level : 9.17 m

RIG:
T45 , KCA Deutag

PERFORATION DATA

ZONE	INTERVAL	STATUS	GUN TYPE	SPF	PHS	DATE
Rotliegend Sst	3140 - 3152.5	done	2" MAX FORCE	6	60	JUL-2012
	3152.5 - 3165					
	3165 - 3176					
	3182 - 3192					
	3192 - 3200					
	3205 - 3214					
Volpriehausen	2707.5 - 2713.5					

© PETROFOCUS LIMITED

PREPARED BY: Henk Craanen | CHECKED BY: Peter Barten / Peter Koppes | DATE: Aug. 2012